

BROTHERS

DRYFILL



UTILITY REQUIREMENT :

Filtered Compressed Air $\,:$ Filtered, Oil Free 2kg/cm2, 5 to 7 Bar Air Pressure

Vacuum : 28" Hg. @ 300 LPM 2nos. and 500LPM 1no.

Humidity : Below 30% Rh

Electrical : 415 VAC 3 Phase 50Hz and 220 VAC Single Phase Power Supply (50/60 Hz) with A.C. Drive

Power : 2 Hp For Machine and 3 Hp for Vacuum Pump if procured with machine.

Note: Required Compressed Air as well as Vaccum Pump / Vaccum Line to be provided by customer only.

Automatic 12 Head Rotary Dry Syrup Powder Filling Machine

The Automatic High Speed *12 Head Rotary Dry Syrup Powder Filling* Machine Model DRYFILL-80R is suitable for Glass, Plastic, PET, HDPE, LDPE Bottles with maximum speed of 80 Bottles per minute depending on Powder Fill Volume, Type of Powder, Bottle Diameter and Bottle Neck Diameter.

Machine in Stainless Steel Finish with heavy duty frame structure with S.S. Cladding. All parts coming in contact with Powders are made from SS316 Materials as well as HDPE Funnels.

The Machine works on proven time tested Vacuum and Air Systems to Fill powder in Bottle achieving higher speed and higher accuracy. Machine with unique Bottle Lifting and Neck Holding system avoid spillage of powder on bottle shoulder, neck and body keeps bottle clean and also avoid wastage of powder.

Machine with complete synchronization of Bottle In-feed StarWheel, Powder Wheel movement and out-feed StarWheel for smoother operation. Machine with Rotary Bottle Moving system ensures very high speed powder filling through independent moving funnel along with bottles for greater speed and performance without compromising speed and fill accuracy. Machines with unique vibratory system inside the funnel helps filling of semi free flow type powder at higher speed.

TECHNICAL SPECIFICATIONS

Bottle Diameter : Upto 85mm*, Square or Rectangular bottles can be used Bottle Height : 100mm* Maximum

Fill Range : 5gms. To 70gms. In Single Dose with the help of change parts for different fill volume

Fill Accuracy : +/- 1 to 2% Depending upon the Powder, under the controlled level of Humidity

Humidity : Below 30% Rh required on machine to be arrange by customer Conveyor Height : 815-940 mm

Overall Dimensions : 2100 mm (L) x 1225 mm (W) x 1800 mm

Speed : Max. 80 Bottles per minute depending on Bottle Size, Bottle Neck Diameter, Type of Powder and Fill Volume.

* Specification can be changed as per customers requirements

SPECIAL / OPTIONAL* FEATURES :

- No Bottle No Fill System
- Rotary Bottle Movement System with Rotary Funnel System
- Funnel with Unique Vibratory system for filling semi free flow powder at higher speed
- All contact parts with easy removal system for Cleaning / Autoclaving / Sterilization
- Machine construction in SS304 material
- Filling Accuracy of +/- 1 to 2% depending on powder at controlled humidity below 30% Rh
- Automatic In-feed and Exit of Bottles through Star Wheel System
- No Bottle at in-feed conveyor Automatic Machine on/off System
- Low Air Machine Stop System
- Low Vacuum Machine Stop System
- Toughened Glass Safety Cabinet*
- Blower for dust extraction

Email : sales@brothers.in Export : sales1@brothers.in

Phone : +91 79 40213213 / 25831346

www.brothersindia.com